

MANUAL OF MOST-OFTEN-NEEDED RADIO DIAGRAMS

COMPILED BY M. N. BEITMAN, SUPREME PUBLICATIONS

219

PART NO.	DESCRIPTION
G1 22-300	365 MMFD. VAR
G2 22-250	.05 MFD. 200K
G3 22-127	.25 MMFD. 600K
G4 22-199	.5 MFD. 200K
G5 22-152	.00025 MMFD. 600K
G6 22-185	.01 MFD. 200K
G7 22-198	.02 MFD. 400K
G8 22-52	.001 MFD. 600K
G9 22-170	.1 MFD. 400K
G10 22-417	.1 MFD. 600K
G11 22-305	.2-35 MMFD
G12 22-292	.0001 MFD. 400K
G13 22-125	.0001 MFD. 400K
G14 22-304	.0036 MFD. 600K
G15 22-435	.02 MFD. 600K

R1 63-280 49M OHMS
R2 63-377 170 OHMS
R3 63-250 49M OHMS
R4 63-293 990 M OHMS
RG 63-377 11M OHMS
RT 63-366 200M VOL CONTROL
R8 63-351 17.025 CANDOHM
R9 63-475 50M TONE CONTROL
R10 63-278 99M OHMS #W.

- 1 53397 SELECTOR DET COIL
- 2 5562 SHORT WAVE SW.
- 3 5-329 OSC COIL ASSEM.
- 4 5-244 1ST I.F. TRANS.
- 5 5-245 2ND I.F. TRANS.
- 6 5-249 6.5 MHZ. 1000-M FIELD - 55-56
- 7 49-61 6.5 MHZ. 1000-M FIELD - 55-29
- 8 5-234 POWER TRANS. 50-60W
- 9 5-229 25W
- 10 93377 16 METER DET COIL

